

**Important** 

**Safety Instructions** 

**IMPORTANT** - The first step you need to take is to ensure your safety! Please

• This item is intended for indoor use only - unless otherwise specified.

• Please keep these instructions for future reference.

• The installation can be completed by non-professionals.

take the time to read and understand these instructions before installing the

During installation children should be kept away from the product due to possi-

• Products can be dangerous if incorrectly fitted or assembled. Installation should

• Restrain children from climbing or playing on or around the product. Always

• Keep all plastic wrapping materials away from babies and children to avoid

• Once items are part or fully installed, they are not returnable unless faulty.

• Ensure that all wall plugs and screws provided are suitable for your type of

• Ensure that all packaging is disposed of carefully and responsibly. Please recycle

• Once a blind has been cut, it cannot be returned - however this does not affect

• Blind head rails should not be installed less than 1.5m from the floor.

be carried out by a competent person and instructions followed. No liability will be accepted for damage or injury caused by incorrectly installed or assembled

consider where products are positioned to ensure children cannot get access to

ble risk of injury. The product may contain small parts that could also cause

### 1. Check you have received all parts supplied listed and the correct quantity of each. Beware that sometimes parts are packaged within the product so not

- immediately visible after opening.
- 2. Please check the installation guide section for more details. If anything is missing, stop installing the product and contact our customer service team. Check all parts are intact and undamaged. Any issues, contact our customer
- Check you have the right tools for the job. Required tools which are not provided are listed overleaf. If you are unsure of how to use these tools, please contact a professional tradesperson. We recommend Airtasker as an easy way to find trades people in your local area.

### Care Advice.

**Getting Started.** 

### Wipe clean only.

Modification of the design or configuration of the blind or its integral or non-integral component parts shall not be made without consulting the manufacturer. Use of the additional safety device helps reduce the risk of strangulation but cannot be considered completely fool proof.


Page 1

# Ruler/Tape Measure Pencil (000 **)**

Tools required which are not included

# Required if cutting down your blind

<u>Dunelm</u>



### Parts supplied.

**Getting Started.** 

Visual


Srrewdriver

**Dunelm** 

**Dunelm** 

**Dunelm** 


Visual		Qty
Pivot End Plug		1
Control Wheel		1
Fixing Bracket and Cover		1
Fixing Bracket and Cover		1



<u>Dunelm</u>

Page 2

# CHILD SAFETY WARNING



Cords may become wrapped around a child's neck. Move beds, cots and furniture

away from window covering cords. Do not tie cords together. Make sure cords do not twist and create a loop.

 PERSONS IN CHARGE OF CHILDREN ARE **ULTIMATELY RESPONSIBLE FOR FOLLOWING THE SAFETY INSTRUCTIONS** PROVIDED BY THE MANUFACTURER AND TO USE ANY SAFETY DEVICE SUPPLIED.

### **Safety Recommendations.**

Installation Guide.

Dunelm

on a flat surface.

and cut the tube.

2. Cutting Down the Blind

**Helpful Hint - For Blackout Blinds only** 

- To help avoid the fabric fraying please

ensure that your scissors are very sharp

and we suggest that you could carefully

the fabric where you are to cut or apply

apply some masking tape to the reverse of

some Hi-Tack Fray Stop Glue. Available at

Ensure hands and work surfaces are clean

before unrolling the blind. Unroll the blind

taking care not to remove the blind from

the inner tube. Place the blind face down

brackets at the widest point. Now minus

3.2cm (32mm) off this measurement as this

will allow for the mechanism. If you are not

sure, please cut less off and adjust again if

Take the scissors and cut along the line to

the top of the blind. Use the craft knife to

cut the fabric attached to the tube. Ensure

scissors and craft knife are sharp enough

for a clean cut. On the inner tube make a

longer than the fabric. Take the hacksaw

Now take the bottom bar and make a cut

cut mark with the pencil 0.5cm (5mm)

pencil and ruler. Ensure that the line is

straight from the top to the bottom.

necessary. Now mark the cut line using the

Measure the distance between the

- Always use a Step Ladder when working at height.
- We recommend you use two people for the installation of larger blinds.
- DO NOT over-reach. DO NOT hold or lean on the blind to support your weight. • Always move the Step Ladder so that you are in a safe working position.
- Take care when using power tools, use of a Residual Current Device (RCD) is
- Always use eye protection when drilling. Beware of hidden pipe runs and cables. No liability will be accepted for damage or injury caused by incorrectly installed or assembled product.
- PLEASE KEEP OUT OF THE REACH OF YOUNG CHILDREN. SMALL PARTS - CHOKING HAZARD.
- Please keep these instructions and batch code from packaging for future reference.

Page 3

eds to be

Safety Advice.

**Dear Customer** 

products.

choking if swallowed.

danger of suffocation.

your statutory rights.

• This blind is maintenance free.

where possible.






Wall fixing guide.

When drilling into walls always check there are no hidden wires or pipes etc. Make sure that the screws and wall plugs being used are suitable for supporting your blind. If you are unsure of the below guidance, consult a qualified tradesperson for advice or help.

- 1. General Rule; Always use a larger screw and wall plug if you are not sure.
- 2. Ensure you use the recommended drill bit to match the wall plug and hole size.
- 3. Ensure you drill the hole horizontally, do not force the drill or enlarge the hole. 4. Take extra care when drilling high walls, ceilings and ceramic tiles. Ensure the
- plug is fitted below the ceramic tile to avoid splitting or cracking. 5. Ensure wall plugs are well fitted and are a tight fit in the drilled hole.

### **Care and Maintenance.**

Regularly check the fixings to ensure the wall plug or screws have not become loose. Tighten or stop using the product if they have.



Page 5

### Installation Guide.


### IMPORTANT - Keep these instructions for future reference

- Our blackout blinds are made with 100% blackout fabric, please note however due to the fixing method, the blind will hang slightly away from the window, therefore the light can still come through the sides of the blind.
- This Roller Blind can be fitted inside or outside the window recess. For improved room darkening it is recommended to fit the blind on the outside of the recess with a minimum of 5cm fabric overlap on each side of the blind. Further improved room darkening can be achieved by layering blinds and curtains together at the window. See our blackout range on dunelm.com
- If cutting down the blind and it has a symmetrical pattern, it is recommended that the fabric is cut on either side to achieve the required width and keep the pattern symmetrical.
- Ensure that all wall plugs and screws provided are suitable for your type of wall/window. If in doubt consult a professional. See wall fixing guide within this
- Make sure the screws and wall plugs used are suitable for your wall type and that they can support the weight of the product. Consult a qualified tradesperson if
- Before drilling into walls, always check there are no hidden wires or pipes behind.

### 1. Measuring your Window

width measurement required for your blind.

This blind can be fitted to the wall outside the recess or inside the window recess. Remember to allow room for the control mechanism and your brackets, when fitting to aid smooth operation If fitting outside of the window recess, measure the width of your blind and add 3.2cm (32mm) to the measurement, as this will allow for the Roller blind mechanism. Make sure the width of the blind overlaps evenly on each side of your window recess. If fitting inside the window recess, measure the top of the window recess where the blind will be fitted. Now minus 3.2cm (32mm) from this measurement, as this will allow for the Roller blind mechanism. This is the total




**Dunelm** 

If you need to cut down your blind see further details in the Cutting Down the

Page 6

evenly rolled at both sides.

To fit the blind, refer back to the installation



Blind

The internal width of window

minus 3.2cm

<u>Dunelm</u>

mark to the same width as the cutdown blind. You can now insert the bottom bar and roll up the blind, make sure to keep it

guide section of this leaflet.

# **Bottom Bar** The same width as fabric 0.5cm

Page 7

## **Installation Guide.**


### **Dunelm**


Page 4

### 3. Fitting the Brackets A. Fitting Brackets Outside the Recess.


wall/window. If in doubt consult a professional.


- 1. Position the bracket at least 5cm above the recess, and 5cm to the side to ensure the fabric overlaps the
- window recess.
- 2. Mark the screw hole with a pencil. 3. Screw holes.
- 4. Fix wall plugs into the holes, add the bracket and screw into place.
- other side.







## **B. Fitting the Brackets Inside the Recess.**












3. Screw holes. 4. Fix wall plugs into the holes, add the bracket and screw into place.

5. Repeat for the second bracket at the other side.

6. Ensure brackets are level.





Installation Guide.

right side of the blind.

to ensure correct operation . 3. Place the pivot end in the other end

Children can strangle if this device is not installed. Read the instructions

Down the Blind.

4. Fitting the Blind to the Brackets

Now the brackets are in place, if the blind needs to be cut down, refer to the section titled Cutting

1. Push the control mechanism in to the left or

2. The chain guard must be positioned at the top

4. Push the pivot end into the bracket, then push

5. Installing the Child Safety Device

the control mechanism into the other bracket.

### 6. Operating the Blind

The blind will now operate by pulling on the beaded cord to raise and lower it.





How to correct fabric run off The illustration shows the fabric running off from the right-hand side of the blind. To correct this, simply stick a small (30mm) strip of masking tape to the aluminium tube at the opposite end. Fully wind the blind up and then repeat until the fabric is no longer running off.



### **Customer service.**

If you have any issues with this product, you can call our Customer Service team on: **0345 165 6565** Monday to Friday **9am to 5:00pm.** 

Alternatively, you can contact our team by Live Chat on: **Dunelm.com** Monday to Friday 8am - 8:30pm Saturdays 8am - 5:30pm Sundays and bank holidays 9am - 4:30pm.



LE7 1AD & Dunelm (Soft Furnishings) Holdings Ltd. Dublin D12 WR25.





# Dunelm (Soft Furnishings) Ltd.

Manufactured in China